



EXCEPT AS OTHERWISE NOTED

ALL DIMENSIONS IN INCHES
 TOLERANCE: .XXX = ± .005 .XX = ± .01

SURFACE FINISH EXCEPT AS NOTED **63** ✓

BREAK EDGES TO DEBURR RADIUS OR CHAMFER .003 MAX

FILLETS - .003 MAX RAD.

THESE DIAS ⊕ TO - T.I.R.

ALL PART NUMBER LETTERSUFFIXES ARE TO BE INTERPRETED AS FOLLOWS:

I.E. - 107-0000-01 (X)

M - MACHINED ONLY (UNPLATED) **G** - MATERIAL HAS BEEN GRAINED
P - PLATED/PAINTED **S** - MATERIAL HAS BEEN SAWCUT
H - HEAT TREATED **E** - ENVIRONMENTAL TEST

		CHATSWORTH, CA.						
		SCALE	2X	REV	-	DATE	-	ECN
DATE		7/17/02		PART NO.		6221A1		
DRAWN		N.C.		CHECKED		R.A.		
MATERIAL		303 ST. STEEL						
APPROVED		NEXT ASSEMBLY			USED ON			
					3033B			
TITLE					DWG NO.			
OUTLINE/INSTALLATION DRAWING, ADHESIVE MOUNTING BASE, MODEL 3033B					127-6221A1			
					SHEET 1 OF 1			